


T = 1.6 mm

- NOTE :
- UNLESS OTHERWISE SPECIFIED, GENERAL TOLERANCES ARE:
 - 0 – 20mm : ± 0.1
 - 21 – 50mm : ± 0.2
 - 51 – 100mm : ± 0.3
 - 101 – 150mm : ± 0.4
 - * INDICATES CONTROL DIMENSIONS.
 - MATERIAL CODE : SECC OR SPCC, THICKNESS = 1.6mm
 - BURRS SHALL NOT EXCEED 0.05mm.
ALL BURRS THAT MAY RESULT IN INJURY SHALL BE REMOVED.
 - UNSPECIFIED CORNER RADIUS TO BE R0.1 MAX.
 - UNSPECIFIED INSIDE BENDING RADIUS TO BE R0.3.
 - ALL BENDING DIMENSION TO MEASURE AT THE TANGENT POINT OF THE BENDS.
 - MATERIAL USED AND PARTS PRODUCED MUST COMPLY ROHS REQUIREMENT.
 - SURFACE TO BE FREE FROM SCRATCHES, DIRT AND OIL.

MATERIAL: SPCC T=1.6				<div><div><div>• DO NOT SCALE DRAWING.</div><div>• IF IN DOUBT, ASK.</div><div>• ALL DIMENSIONS IN mm.</div></div><div></div></div>	IR ROBOT	
PROCESS: ZnC PLATING					(Private and Confidential) Copyright ©2013	
COLOUR: LIGHT BLUE				VOLUME [mm³] :	PART NAME : BRACKET C, IR-MB03&07	
DRAWN	NAME	SIGNATURE	DATE		PART NO :	REV NO:
CHK'D	YC KIM		2024. 08.26	WEIGHT [gf] :	IRMIS0005	05
APPV'D					SCALE 2:1	SHEET 2 OF 2
						A3